



# DP1.5N-TR

DIN Rail Terminal Blocks &gt; Push-in Design

Date:2026-03-23Version:V1.2



The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.  
The final product is made according to engineering drawing.

## Product Description

300V, 15A, Beige (default)

## General information

|                     |                                                          |
|---------------------|----------------------------------------------------------|
| Short description   | Single level Feed-Through Terminal Block, Push-in Design |
| Category            | Single level Feed Through Terminal Block                 |
| Color               | Beige (default)                                          |
| Connection method   | Push-in Design                                           |
| Type of locking     | Rail mounting                                            |
| Length (mm)         | 69.5                                                     |
| Width (mm)          | 3.5                                                      |
| Height (mm)         | 30.6                                                     |
| Number of positions | ≥1P                                                      |
| Level               | Single level                                             |
| Connection points   | 4                                                        |

## Material information

|                           |    |
|---------------------------|----|
| Insulation material       | PA |
| Insulation material group | I  |

|                                              |                                     |
|----------------------------------------------|-------------------------------------|
| Flame retardant rating , compliant with UL94 | V0                                  |
| Insulation resistance                        | $\geq 500\text{M}\Omega$ at DC 500V |

## Connection data-IEC

|                                                                                              |         |
|----------------------------------------------------------------------------------------------|---------|
| Rated voltage (V)                                                                            | 500     |
| Rated current (A)                                                                            | 17.5    |
| Rated voltage (III/3)(V)                                                                     | 500     |
| Rated impulse voltage (III/3)(KV)                                                            | 6       |
| Conductor cross section solid. min (mm <sup>2</sup> )                                        | 0.14    |
| Conductor cross section solid.max (mm <sup>2</sup> )                                         | 1.5     |
| Conductor cross section stranded. min (mm <sup>2</sup> )                                     | 0.14    |
| Conductor cross section stranded. max (mm <sup>2</sup> )                                     | 1.5     |
| Conductor cross section flexible, with min ferrule without plastic sleeve (mm <sup>2</sup> ) | 0.25    |
| Conductor cross section flexible, with max ferrule without plastic sleeve (mm <sup>2</sup> ) | 1.5     |
| Conductor cross section flexible, with min ferrule with plastic sleeve (mm <sup>2</sup> )    | 0.25    |
| Conductor cross section flexible, with max ferrule with plastic sleeve (mm <sup>2</sup> )    | 0.75    |
| Slotted screwdriver size (Blade thickness x Width)(mm)                                       | 0.4x2.5 |
| Stripping Length (mm)                                                                        | 8       |
| Mounting rail                                                                                | TS-35   |
| End cover plate required                                                                     | YES     |
| Grounding connections                                                                        | NO      |

## Connection data-UL

|                                                  |     |
|--------------------------------------------------|-----|
| Rated voltage (UL/CUL Group B)(V)                | 300 |
| Rated current (UL/CUL Group B)(A)                | 15  |
| Rated voltage (UL/CUL Group C)(V)                | 300 |
| Rated current (UL/CUL Group C)(A)                | 15  |
| Min. solid wire connection (AWG) acc. to UL/CUL  | 26  |
| Max. solid wire connection AWG acc. to UL/CUL    | 14  |
| Min. stranded wire connection AWG acc. to UL/CUL | 26  |
| Max. stranded wire connection AWG acc. to UL/CUL | 14  |

## Environment & Safety

|                                         |     |
|-----------------------------------------|-----|
| Back of the hand protection (YES or NO) | YES |
| Finger protection (YES or NO)           | YES |
| Operating temperature. max (°C)         | 120 |
| Operating temperature. min (°C)         | -40 |


## UL Recognized

|                            |       |
|----------------------------|-------|
| Wire Range (Group B)(AWG)  | 26~14 |
| Rated voltage (Group B)(V) | 300   |
| Rated current (Group B)(A) | 15    |
| Wire Range (Group C)(AWG)  | 26~14 |
| Rated voltage (Group C)(V) | 300   |
| Rated current (Group C)(A) | 15    |

## CUL Recognized

|                            |       |
|----------------------------|-------|
| Wire Range (Group B)(AWG)  | 26~14 |
| Rated voltage (Group B)(V) | 300   |
| Rated current (Group B)(A) | 15    |
| Wire Range (Group C)(AWG)  | 26~14 |
| Rated voltage (Group C)(V) | 300   |
| Rated current (Group C)(A) | 15    |

## Drawings



## Approvals

