


# ED130R-XXP

PCB Terminal Blocks &gt; PCB Connector-Plug

Date:2026-03-23Version:1.1



The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.  
The final product is made according to engineering drawing.

## Product Description

Pitch : 5.00 mm, 300V, 12A

## General information

|                     |                                           |
|---------------------|-------------------------------------------|
| Short description   | PCB Connector – Plug, Wire protector type |
| Category            | PCB Connector – Plug                      |
| Pitch (mm)          | 5.00                                      |
| Color               | Black (default)                           |
| Connection method   | Wire Protector Type                       |
| Type of locking     | Without                                   |
| Length (mm)         | 5.00*P                                    |
| Width (mm)          | 14.7                                      |
| Height (mm)         | 12.5                                      |
| Number of positions | 02P~20P                                   |
| Level               | Single level                              |

## Material information

|                                              |    |
|----------------------------------------------|----|
| Insulation material                          | PA |
| Insulation material group                    | I  |
| Flame retardant rating , compliant with UL94 | V0 |

|                              |                   |
|------------------------------|-------------------|
| Insulation resistance        | □500MΩ at DC 500V |
| Conductor material           | COPPER ALLOY      |
| Plating of conductor surface | Tin PLATED        |

## Connection data-IEC

|                                                                                                           |     |
|-----------------------------------------------------------------------------------------------------------|-----|
| Rated voltage (V)                                                                                         | 320 |
| Rated current (A)                                                                                         | 10  |
| Rated voltage (II/2)(V)                                                                                   | 400 |
| Rated voltage (III/2) (V)                                                                                 | 320 |
| Rated voltage (III/3)(V)                                                                                  | 250 |
| Rated impulse voltage (II/2)(KV)                                                                          | 4   |
| Rated impulse voltage (III/2)(KV)                                                                         | 4   |
| Rated impulse voltage (III/3)(KV)                                                                         | 4   |
| Conductor cross section solid. min (mm <sup>2</sup> )                                                     | 0.5 |
| Conductor cross section solid.max (mm <sup>2</sup> )                                                      | 1.5 |
| Conductor cross section stranded. min (mm <sup>2</sup> )                                                  | 0.5 |
| Conductor cross section stranded. max (mm <sup>2</sup> )                                                  | 1.5 |
| Conductor cross section flexible, with min ferrule without plastic sleeve (mm <sup>2</sup> )              | 0.5 |
| Conductor cross section flexible, with max ferrule without plastic sleeve (mm <sup>2</sup> )              | 1   |
| Conductor cross section flexible, with min ferrule with plastic sleeve (mm <sup>2</sup> )                 | 0.5 |
| Conductor cross section flexible, with max ferrule with plastic sleeve (mm <sup>2</sup> )                 | 1   |
| 2 conductors with same cross section, solid, min (mm <sup>2</sup> )                                       | 0.5 |
| 2 conductors with same cross section, solid, max (mm <sup>2</sup> )                                       | 1   |
| 2 conductors with same cross section, stranded, min (mm <sup>2</sup> )                                    | 0.5 |
| 2 conductors with same cross section, stranded, max (mm <sup>2</sup> )                                    | 1   |
| 2 conductors with same cross section flexible, with min ferrule without plastic sleeve (mm <sup>2</sup> ) | 0.5 |
| 2 conductors with same cross section flexible, with max ferrule without plastic sleeve (mm <sup>2</sup> ) | 0.5 |
| 2 conductors with same cross section flexible, min twin ferrules with plastic sleeve (mm <sup>2</sup> )   | 0.5 |
| 2 conductors with same cross section flexible, max twin ferrules with plastic sleeve (mm <sup>2</sup> )   | 0.5 |

|                                                        |         |
|--------------------------------------------------------|---------|
| Screw thread                                           | M2.5    |
| Slotted screwdriver size (Blade thickness x Width)(mm) | 0.6x3.5 |
| Philips screwdriver size                               | PH1     |
| Rated torque (N.m)                                     | 0.3     |
| Stripping Length (mm)                                  | 5~6     |

## Connection data-UL

|                                                  |     |
|--------------------------------------------------|-----|
| Rated voltage (UL/CUL Group B)(V)                | 300 |
| Rated current (UL/CUL Group B)(A)                | 12  |
| Rated voltage (UL/CUL Group D)(V)                | 300 |
| Rated current (UL/CUL Group D)(A)                | 10  |
| Min. solid wire connection (AWG) acc. to UL/CUL  | 22  |
| Max. solid wire connection AWG acc. to UL/CUL    | 14  |
| Min. stranded wire connection AWG acc. to UL/CUL | 22  |
| Max. stranded wire connection AWG acc. to UL/CUL | 14  |

## Environment & Safety

|                                 |     |
|---------------------------------|-----|
| Finger protection (YES or NO)   | YES |
| Operating temperature. max (°C) | 120 |
| Operating temperature. min (°C) | -40 |

## UL Recognized

|                            |       |
|----------------------------|-------|
| Wire Range (Group B)(AWG)  | 22~14 |
| Rated voltage (Group B)(V) | 300   |
| Rated current (Group B)(A) | 12    |
| Wire Range (Group D)(AWG)  | 22~14 |
| Rated voltage (Group D)(V) | 300   |
| Rated current (Group D)(A) | 10    |


## CUL Recognized

|                            |       |
|----------------------------|-------|
| Wire Range (Group B)(AWG)  | 22~14 |
| Rated voltage (Group B)(V) | 300   |
| Rated current (Group B)(A) | 12    |
| Wire Ranget (Group D)(AWG) | 22~14 |
| Rated voltage (Group D)(V) | 300   |

Rated current (Group D)(A)

10

## Drawings



## Approvals

