


# 5ESDG-XXP

PCB Terminal Blocks &gt; PCB Connector-Plug

Date:2026-03-23Version:1.1



The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.  
The final product is made according to engineering drawing.

## Product Description

Pitch : 5.00 mm, 300V, 16A

## General information

|                     |                                        |
|---------------------|----------------------------------------|
| Short description   | PCB Connector – Plug, Screw Connection |
| Category            | PCB Connector – Plug                   |
| Pitch (mm)          | 5.00                                   |
| Color               | Green (default)                        |
| Connection method   | Screw Connection                       |
| Type of locking     | PCB Connection                         |
| Length (mm)         | 5.00*P                                 |
| Width (mm)          | 18.4                                   |
| Height (mm)         | 15.5                                   |
| Number of positions | 02P~14P                                |
| Level               | Single level                           |

## Material information

|                                              |    |
|----------------------------------------------|----|
| Insulation material                          | PA |
| Insulation material group                    | I  |
| Flame retardant rating , compliant with UL94 | V0 |

|                              |                   |
|------------------------------|-------------------|
| Insulation resistance        | □500MΩ at DC 500V |
| Conductor material           | COPPER ALLOY      |
| Plating of conductor surface | Tin PLATED        |

## Connection data-IEC

|                                                                                                           |         |
|-----------------------------------------------------------------------------------------------------------|---------|
| Rated voltage (V)                                                                                         | 400     |
| Rated current (A)                                                                                         | 12      |
| Rated voltage (II/2)(V)                                                                                   | 400     |
| Rated voltage (III/2) (V)                                                                                 | 160     |
| Rated voltage (III/3)(V)                                                                                  | 160     |
| Rated impulse voltage (II/2)(KV)                                                                          | 2.5     |
| Rated impulse voltage (III/2)(KV)                                                                         | 2.5     |
| Rated impulse voltage (III/3)(KV)                                                                         | 2.5     |
| Conductor cross section solid. min (mm <sup>2</sup> )                                                     | 0.32    |
| Conductor cross section solid.max (mm <sup>2</sup> )                                                      | 2.5     |
| Conductor cross section stranded. min (mm <sup>2</sup> )                                                  | 0.32    |
| Conductor cross section stranded. max (mm <sup>2</sup> )                                                  | 2.5     |
| Conductor cross section flexible, with min ferrule without plastic sleeve (mm <sup>2</sup> )              | 0.25    |
| Conductor cross section flexible, with max ferrule without plastic sleeve (mm <sup>2</sup> )              | 2.5     |
| Conductor cross section flexible, with min ferrule with plastic sleeve (mm <sup>2</sup> )                 | 0.25    |
| Conductor cross section flexible, with max ferrule with plastic sleeve (mm <sup>2</sup> )                 | 2.5     |
| 2 conductors with same cross section, solid, max (mm <sup>2</sup> )                                       | 1.5     |
| 2 conductors with same cross section, stranded, max (mm <sup>2</sup> )                                    | 1.5     |
| 2 conductors with same cross section flexible, with min ferrule without plastic sleeve (mm <sup>2</sup> ) | 0.25    |
| 2 conductors with same cross section flexible, with max ferrule without plastic sleeve (mm <sup>2</sup> ) | 0.75    |
| 2 conductors with same cross section flexible, min twin ferrules with plastic sleeve (mm <sup>2</sup> )   | 0.5     |
| 2 conductors with same cross section flexible, max twin ferrules with plastic sleeve (mm <sup>2</sup> )   | 1.5     |
| Screw thread                                                                                              | M2.5    |
| Slotted screwdriver size (Blade thickness x Width)(mm)                                                    | 0.6x3.5 |
| Philips screwdriver size                                                                                  | PH1     |

|                       |      |
|-----------------------|------|
| Rated torque (N.m)    | 0.45 |
| Stripping Length (mm) | 7~8  |

## Connection data-UL

|                                                  |     |
|--------------------------------------------------|-----|
| Rated voltage (UL/CUL Group B)(V)                | 300 |
| Rated current (UL/CUL Group B)(A)                | 16  |
| Rated voltage (UL/CUL Group D)(V)                | 300 |
| Rated current (UL/CUL Group D)(A)                | 10  |
| Min. solid wire connection (AWG) acc. to UL/CUL  | 28  |
| Max. solid wire connection AWG acc. to UL/CUL    | 12  |
| Min. stranded wire connection AWG acc. to UL/CUL | 28  |
| Max. stranded wire connection AWG acc. to UL/CUL | 12  |

## Environment & Safety

|                                 |     |
|---------------------------------|-----|
| Finger protection (YES or NO)   | YES |
| Operating temperature. max (°C) | 120 |
| Operating temperature. min (°C) | -40 |

## UL Recognized



|                            |       |
|----------------------------|-------|
| Wire Range (Group B)(AWG)  | 28~12 |
| Rated voltage (Group B)(V) | 300   |
| Rated current (Group B)(A) | 16    |

## CUL Recognized

|                            |       |
|----------------------------|-------|
| Wire Range (Group B)(AWG)  | 28~12 |
| Rated voltage (Group B)(V) | 300   |
| Rated current (Group B)(A) | 16    |

## Drawings

|  |  |
|--|--|
|  |  |
|--|--|



## Approvals

