


# ECH381RM-XXP

PCB Terminal Blocks > PCB Connector-Socket

Date:2026-03-23Version:V1



The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.  
The final product is made according to engineering drawing.

## Product Description

Pitch : 3.81 mm, 300V, 8A

## General information

|                                        |                                        |
|----------------------------------------|----------------------------------------|
| Short description                      | PCB Connector – Socket, Wave soldering |
| Category                               | PCB Connector – Socket                 |
| Pitch (mm)                             | 3.81                                   |
| Color                                  | Green (default)                        |
| Type of locking                        | With threaded flange                   |
| Soldering method                       | Wave soldering                         |
| Length (mm)                            | $3.81 \times (P-1) + 14.4$             |
| Width (mm)                             | 9.2                                    |
| Height (mm)                            | 7.2                                    |
| Pin demensions (Thickness x Width)(mm) | 0.8x0.8                                |
| PCB hole diameter (mm)                 | 1.2~1.3                                |
| Number of positions                    | 02P~24P                                |
| Level                                  | Single level                           |

## Material information

|                     |    |
|---------------------|----|
| Insulation material | PA |
|---------------------|----|

|                                              |                   |
|----------------------------------------------|-------------------|
| Insulation material group                    | I                 |
| Flame retardant rating , compliant with UL94 | V0                |
| Insulation resistance                        | □500MΩ at DC 500V |
| Conductor material                           | COPPER ALLOY      |
| Plating of conductor surface                 | Tin PLATED        |

## Connection data-IEC

|                                          |     |
|------------------------------------------|-----|
| Rated voltage (V)                        | 500 |
| Rated current (A)                        | 14  |
| Rated voltage (II/2)(V)                  | 500 |
| Rated voltage (III/2) (V)                | 320 |
| Rated voltage (III/3)(V)                 | 200 |
| Rated impulse voltage (II/2)(KV)         | 2.5 |
| Rated impulse voltage (III/2)(KV)        | 2.5 |
| Rated impulse voltage (III/3)(KV)        | 2.5 |
| Tightening torque with flange. max (N.m) | 0.3 |

## Connection data-UL

|                                   |     |
|-----------------------------------|-----|
| Rated voltage (UL/CUL Group B)(V) | 300 |
| Rated current (UL/CUL Group B)(A) | 8   |
| Rated voltage (UL/CUL Group D)(V) | 300 |
| Rated current (UL/CUL Group D)(A) | 8   |

## Environment & Safety

|                                 |     |
|---------------------------------|-----|
| Finger protection (YES or NO)   | YES |
| Operating temperature. max (°C) | 120 |
| Operating temperature. min (°C) | -40 |

## UL Recognized

|                            |     |
|----------------------------|-----|
| Rated voltage (Group B)(V) | 300 |
| Rated current (Group B)(A) | 8   |
| Rated voltage (Group D)(V) | 300 |
| Rated current (Group D)(A) | 8   |


## CUL Recognized

|                            |     |
|----------------------------|-----|
| Rated voltage (Group B)(V) | 300 |
| Rated current (Group B)(A) | 8   |
| Rated voltage (Group D)(V) | 300 |
| Rated current (Group D)(A) | 8   |

## VDE Approval

|                   |     |
|-------------------|-----|
| Rated voltage (V) | 320 |
| Rated current (A) | 14  |

## Drawings



## Approvals

