

TFT DISPLAY SPECIFICATION



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司



Winstar Display Co., LTD

華凌光電股份有限公司



WEB: <https://www.winstar.com.tw> E-mail: sales@winstar.com.tw

SPECIFICATION

MODULE NO.: WF57A5TYAFDNT0#

General Specifications

Item	Dimension	Unit
Size	5.7	inch
Dot Matrix	640 x RGB x 480(TFT)	dots
Module dimension	124.7 x 100.0 x 7.41	mm
Active area	115.2 x 86.4	mm
Pixel pitch	0.18 x 0.18	mm
LCD type	TFT, Normally black, Transmissive	
View Angle	80/80/80/80	
TFT Driver IC	JD9168S or Equivalent	
TFT interface	RGB18bits SYNC+DE mode	
Aspect Ratio	4:3	
Backlight Type	LED, Normally White	
Touch Panel	Resistive Touch Panel	
Surface	Anti-Glare	

*Color tone slight changed by temperature and driving voltage.

Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	°C
Storage Temperature	TST	-30	—	+80	°C

Electrical Characteristics

1. Operating conditions:

Parameter		Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage		VCC	Ta=25°C	3.0	3.3	3.6	V
Input voltage	H	VIH	VCC=3.0V	0.7VCC	-	VCC	
	L	VIL	VCC=3.0V	0	-	0.3VCC	mW
Power supply Current (Operating)		ICC	VCC=3.0V	—	50	75	mA

Note1 ALL White Display pattern

2. LED driving conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit
LED current	-	-	80	-	mA
Power Consumption	-	1344	1440	1536	mW
LED voltage	VLED+	16.8	18.0	19.2	V
LED Life Time	-	50,000	-	-	Hr

Interface

1. LCM PIN Definition

Pin	Symbol	I/O	Function
1	GND	P	Ground.
2	VCC	P	Power supply for TFT
3	VCC	P	Power supply for TFT
4	GND	P	Ground.
5	NC	-	No connection
6	GND	P	Ground.
7	NC	-	No connection
8	GND	P	Ground.
9	UD	I	Up/down selection
10	LR	I	Left /right selection
11	/CSX	I	Chip select pin. 0: Chip can be accessed; 1: Chip cannot be accessed. If this pin is not used, please connect it to VCC.
12	SCL	I	Serial clock input in SPI interface .If not use, let it open or VCC or GND.
13	SDA	I	Serial data input / output pin in SPI interface operation. If not use, let it open.
14	NC	-	No connection
15	GND	P	Ground.
16	B5	I	Blue Data bus
17	B4	I	Blue Data bus
18	B3	I	Blue Data bus
19	B2	I	Blue Data bus
20	B1	I	Blue Data bus
21	B0	I	Blue Data bus
22	NC	-	No connection
23	NC	-	No connection
24	GND	P	Ground.
25	G5	I	Green Data bit
26	G4	I	Green Data bit
27	G3	I	Green Data bit
28	G2	I	Green Data bit

29	G1	I	Green Data bit
30	G0	I	Green Data bit
31	NC	-	No connection
32	NC	-	No connection
33	GND	P	Ground.
34	NC	-	No connection
35	NC	-	No connection
36	GND	P	Ground.
37	R5	I	Red Data bit
38	R4	I	Red Data bit
39	R3	I	Red Data bit
40	R2	I	Red Data bit
41	R1	I	Red Data bit
42	R0	I	Red Data bit
43	VLED-	P	Power supply for LED cathode
44	VLED+	P	Power supply for LED anode
45	DE	I	Data enable input in RGB interface.
46	CLK	I	Pixel clock input in RGB interface.
47	HS	I	Horizontal sync input in RGB interface.
48	VS	I	Vertical sync input in RGB interface
49	NC	-	No connection
50	GND	P	Ground.

TFT FPC

PIN NO.	SYMBOL	PIN NO.	SYMBOL
1	GND	26	G4
2	VCC	27	G3
3	VCC	28	G2
4	GND	29	G1
5	NC	30	G0
6	GND	31	NC
7	NC	32	NC
8	GND	33	GND
9	UD	34	NC
10	LR	35	NC
11	/CSX	36	GND
12	SCL	37	R5
13	SDA	38	R4
14	NC	39	R3
15	GND	40	R2
16	B5	41	R1
17	B4	42	R0
18	B3	43	VLED-
19	B2	44	VLED+
20	B1	45	DE
21	B0	46	CLK
22	NC	47	HS
23	NC	48	VS
24	GND	49	NC
25	G5	50	GND

RTP FPC

PIN NO.	SYMBOL
1	XL
2	YD
3	XR
4	YU

The non-specified tolerance of dimension is ±0.3 mm .